DIRECT-DRIVE EXHAUST VENTILATION

MPF-2400 WALL FAN

Direct-drive ventilation for dependable barn airflow

5,961
CFM @ 0.05 SP

220V
VOLTAGE



Black Housing | White Housing

PRACTICAL, EVERYDAY PERFORMANCE

Slanted Housing
Slanted housing design drains water and condensation away from the barn.

Cleaner Wall Installation
Fans mount flush with inside barn wall.

Protected Motor Design
CSA-approved, epoxy-coated, totally enclosed air-over motor with thermal overload protection.

Durable Bearings
Double-sealed, permanently lubricated ball bearings.

TECHNICAL SPECIFICATIONS

MODEL	MPF-2400
MOTOR	Multifan/Direct Drive
VOLTAGE	220 V
FULL-LOAD AMPS	3.0 A
SPEED	1,000 RPM
AIRFLOW	5,961 CFM @ 0.05 SP
ROUGH-IN DIMENSIONS	27.25 in. W × 27.25 in. L
HOUSING	Durable Polyethylene
SHIPPING WEIGHT	62 lb
CERTIFICATION	CSA Approved

AVAILABLE ACCESSORIES



FS-24
Exhaust Shutter



FC-24
Fan Cover



FH-24
Weather Hood



WC-24
Winter Cover

BUILT FOR LONG-TERM USE
CSA approved • One-year conditional guarantee

BETTER AIR | MacGregor, Manitoba, Canada
info@betterair.ca • betterair.ca • 204-252-2333