DIRECT-DRIVE EXHAUST VENTILATION

LPF-1200 WALL FAN

Direct-drive ventilation for dependable barn airflow

1,725
CFM @ 0.05 SP

115/230V
DUAL VOLTAGE



Black Housing



White Housing

PRACTICAL, EVERYDAY PERFORMANCE

Slanted Housing
Projects 12 in. from the outside of the barn.

Cleaner Wall Installation
Condensation drains down and away from the barn; inside mounting is flush.

Protected Motor Design
Epoxy-coated, totally enclosed air-over motor with thermal overload protection.

Durable Bearings
Double-sealed, permanently lubricated ball bearings.


TECHNICAL SPECIFICATIONS

MODEL	LPF-1200
MOTOR	AGI/Multifan
VOLTAGE	115 / 230 V
FULL-LOAD AMPS	2.6 / 1.3 A
SPEED	1,625 RPM
AIRFLOW	1,725 CFM @ 0.05 SP
ROUGH IN DIMENSIONS	15.25 in. W × 15.25 in. L
HOUSING	Durable Polyethylene
SHIPPING WEIGHT	39 lb
CERTIFICATION	CSA Approved

AVAILABLE ACCESSORIES




FS-12
Exhaust Shutter



FC-16
Fan Cover



FH-12
Weather Hood



WC-12
Winter Cover

BUILT FOR LONG-TERM USE
CSA approved • One-year conditional guarantee

BETTER AIR | MacGregor, Manitoba, Canada
info@betterair.ca • betterair.ca • 204-252-2333