DIRECT-DRIVE EXHAUST VENTILATION

LPF-1600 WALL FAN

Direct-drive ventilation for dependable barn airflow

2,612	220V
CFM @ 0.05 SP	VOLTAGE



Black Housing



White Housing

PRACTICAL, EVERYDAY PERFORMANCE

Slanted Housing
Projects 12 in. from the outside of the barn.

Cleaner Wall Installation
Condensation drains down and away from the barn; inside mounting is flush.

Protected Motor Design
Epoxy-coated, totally enclosed air-over motor with thermal overload protection.

Durable Bearings
Double-sealed, permanently lubricated ball bearings.


TECHNICAL SPECIFICATIONS

MODEL	LPF-1600
MOTOR	AGI/Multifan
VOLTAGE	220 V
FULL-LOAD AMPS	2.6 / 1.3 A
SPEED	1,600 RPM
AIRFLOW	2,612 CFM @ 0.05 SP
ROUGH IN DIMENSIONS	19.25 in. W × 19.25 in. L
HOUSING	Durable Polyethylene
SHIPPING WEIGHT	37 lb
CERTIFICATION	CSA Approved

AVAILABLE ACCESSORIES




FS-16
Exhaust Shutter



FC-16
Fan Cover



FH-16
Weather Hood



WC-16
Winter Cover

BUILT FOR LONG-TERM USE
CSA approved • One-year conditional guarantee

BETTER AIR | MacGregor, Manitoba, Canada
info@betterair.ca • betterair.ca • 204-252-2333