DIRECT-DRIVE EXHAUST VENTILATION

LPF-2800 WALL FAN


Direct-drive ventilation for dependable barn airflow

7,030
CFM @ 0.05 SP

115/230V
DUAL VOLTAGE



Black Housing



White Housing

PRACTICAL, EVERYDAY PERFORMANCE

Slanted Housing
Projects 12 in. from the outside of the barn.

Cleaner Wall Installation
Condensation drains down and away from the barn; inside mounting is flush.

Protected Motor Design
Epoxy-coated, totally enclosed air-over motor with thermal overload protection.

Durable Bearings
Double-sealed, permanently lubricated ball bearings.


TECHNICAL SPECIFICATIONS

MODEL	LPF-2800
MOTOR	AGI/Multifan
VOLTAGE	115 / 230 V
FULL-LOAD AMPS	5.2 / 2.6 A
SPEED	1,075 RPM
AIRFLOW	7,030 CFM @ 0.05 SP
ROUGH IN DIMENSIONS	35 in. W × 35 in. L
HOUSING	Durable Polyethylene
SHIPPING WEIGHT	74 lb
CERTIFICATION	CSA Approved

AVAILABLE ACCESSORIES




FS-28
Exhaust Shutter



FC-28
Fan Cover



FH-28
Weather Hood



WC-28
Winter Cover

BUILT FOR LONG-TERM USE
CSA approved • One-year conditional guarantee

BETTER AIR | MacGregor, Manitoba, Canada
info@betterair.ca • betterair.ca • 204-252-2333