DIRECT-DRIVE EXHAUST VENTILATION

LPF-2800 WALL FAN

Direct-drive ventilation for dependable barn airflow

7,030
CFM @ 0.05 SP

115/230V
DUAL VOLTAGE



Black Housing | White Housing

PRACTICAL, EVERYDAY PERFORMANCE

Slanted Housing
Slanted housing design drains water and condensation away from the barn.

Cleaner Wall Installation
Fans mount flush with inside barn wall.

Protected Motor Design
CSA-approved, epoxy-coated, totally enclosed air-over motor with thermal overload protection.

Durable Bearings
Double-sealed, permanently lubricated ball bearings.


TECHNICAL SPECIFICATIONS

MODEL	LPF-2800
MOTOR	AGI/Multifan
VOLTAGE	115 / 230 V
FULL-LOAD AMPS	5.2 / 2.6 A
SPEED	1,075 RPM
AIRFLOW	7,030 CFM @ 0.05 SP
ROUGH-IN DIMENSIONS	35 in. W × 35 in. L
HOUSING	Durable Polyethylene
SHIPPING WEIGHT	74 lb
CERTIFICATION	CSA Approved

AVAILABLE ACCESSORIES




FS-28
Exhaust Shutter



FC-28
Fan Cover



FH-28
Weather Hood



WC-28
Winter Cover

BUILT FOR LONG-TERM USE
CSA approved • One-year conditional guarantee

BETTER AIR | MacGregor, Manitoba, Canada
info@betterair.ca • betterair.ca • 204-252-2333